

AMENDMENTS TO CLAIMS

Claim 1 (currently amended): An automotive seatback system, comprising:
a first panel having a main wall;
a plurality of primary planar ribs positioned upon the first panel; and
a plurality of channel forming ribs extending along the main wall of the first panel wherein the channel forming ribs form tubular structures in conjunction with the main wall.

Claim 2 (original): An automotive seatback system as in claim 1 wherein the first panel, the primary planar ribs and the plurality of channel forming ribs are integrally molded together of a plastic material.

Claim 3 (original): An automotive seatback system as in claim 2 wherein the plastic material includes a plastic selected from the group of styrene, polyamide, polyolefin, polycarbonate, polyester, acrylonitrile butadiene styrene, polycarbonate/acrylonitrile/butadiene styrene, polycarbonate, polyphenylene oxide/polystyrene, polybutylene terephthalate, polyphenylene oxide, polyphenylene ether, syndiotactic polystyrene, ethylene alpha olefin, polybutylene terephthalate/polycarbonate, polypropylene, polyethylene and mixtures thereof.

Claim 4 (original): An automotive seatback system as in claim 2 wherein each of the channel forming ribs is formed by gas assist injection molding.

Claim 5 (original): An automotive seatback system as in claim 1 further comprising a plurality of attachment locations defined upon the first panel, each of the attachment locations including a plurality of secondary planar ribs.

Claim 6 (currently amended): An automotive seatback system as in claim 1 further comprising an attachment system rotatably attaching the ~~the~~ first panel to an automotive vehicle, the attachment system including:

- i) a plurality of attachment locations, each of the attachment location including at least one looped fastener; and
- ii) a rod extending at least partially through the at least one looped fastener of each of the plurality of attachment locations; and
- iii) a pair of brackets attached to the vehicle and the rod.

Claim 7 (original): An automotive seatback system as in claim 1 wherein at least one of the primary planar ribs extends about the periphery of the first panel.

Claim 8 (original): An automotive seatback system as in claim 1 wherein at least two of the primary planar ribs extend across the main wall in a criss-cross pattern.

Claim 9 (original): An automotive seatback system as in claim 5 wherein one or more of the plurality of channel forming ribs extend between at least two of the plurality of attachment locations.

Claim 10 (original): An automotive seatback system as in claim 6 wherein one or more of the plurality of channel forming ribs extend between at least two of the plurality of attachment locations.

Claim 11 (original): An automotive seatback system as in claim 1 wherein the plurality of channel forming ribs are arc-shaped in cross-section.

Claim 12 (currently amended): An automotive seatback system, comprising:
a first panel having a main wall;
a plurality of primary planar ribs positioned upon the first panel wherein:

- i) at least one of the primary planar ribs extends about the periphery of the first panel;
- ii) at least two of the primary planar ribs extend across the main wall in a criss-cross pattern; and
- iii) the primary planar ribs are integrally formed with the main wall of the same material;

a plurality of attachment locations defined upon the first panel, each of the attachment locations including a plurality of secondary planar ribs;

a plurality of channel forming ribs extending along the main wall of the first panel, at least one of the plurality of channel forming ribs extending at least partially between two of the plurality of attachment locations wherein the first panel is at least part of a seatback within an automotive vehicle.

Claim 13 (original): An automotive seatback system as in claim 12 wherein the first panel, the primary planar ribs and the plurality of channel forming ribs are integrally molded together of a plastic material.

Claim 14 (original): An automotive seatback system as in claim 13 wherein the plastic material includes a plastic selected from the group of styrene, polyamide, polyolefin, polycarbonate, polyester, acrylonitrile butadiene styrene, polycarbonate/acrylonitrile/butadiene styrene, polycarbonate, polyphenylene oxide/polystyrene, polybutylene terephthalate, polyphenylene oxide, polyphenylene ether, syndiotactic polystyrene, ethylene alpha olefin, polybutylene terephthalate/polycarbonate, polypropylene, polyethylene and mixtures thereof.

Claim 15 (original): An automotive seatback system as in claim 12 wherein each of the channel forming ribs is formed by gas assist injection molding.

Claim 16 (original): An automotive seatback system as in claim 12 wherein the plurality of channel forming ribs are arc-shaped in cross-section.

Claim 17 (original): An automotive seatback system, comprising:

a first panel having a main wall;

a plurality of primary planar ribs positioned upon the first panel wherein:

- i) at least one of the primary planar ribs extends about the periphery of the first panel;
- ii) at least two of the primary planar ribs extend across the main wall in a criss-cross pattern; and

iii) the primary planar ribs are integrally formed with the main wall of the same material;

a plurality of attachment locations defined upon the first panel, each of the attachment locations including a plurality of secondary planar ribs;

a plurality of channel forming ribs extending along the main wall of the first panel, at least one of the plurality of channel forming ribs extending at least partially between two of the plurality of attachment locations;

a second panel having a main wall, the second panel laterally adjacent to the first panel for spanning a lateral distance of the seat back system; and

a plurality of channel forming ribs extending along the main wall of the second panel.

Claim 18 (original): An automotive seatback system as in claim 17 wherein the second panel and the plurality of channel forming ribs of the second panel are integrally molded together of a plastic material.

Claim 19 (original): An automotive seatback system as in claim 18 wherein the plastic material includes a plastic selected from the group of styrene, polyamide, polyolefin, polycarbonate, polyester, acrylonitrile butadiene styrene, polycarbonate/acrylonitrile/butadiene styrene, polycarbonate, polyphenylene oxide/polystyrene, polybutylene terephthalate, polyphenylene oxide, polyphenylene ether, syndiotactic polystyrene, ethylene alpha olefin, polybutylene terephthalate/polycarbonate, polypropylene, polyethylene and mixtures thereof.

Claim 20 (original): An automotive seatback system as in claim 19 wherein each of the channel forming ribs is formed by gas assist injection molding.

Claim 21 (currently amended): An automotive seatback system as in claim 20 42 wherein each of the channel forming ribs is arc-shaped in cross-section.

Claim 22 (new): An automotive seatback system as in claim 12 wherein the channel forming ribs form tubular structures in conjunction with the main wall.

Claim 23 (new): An automotive seatback system as in claim 17 wherein the channel forming ribs form tubular structures in conjunction with the main wall.

Claim 24 (new): An automotive seatback system as in claim 1 wherein the first panel is at least part of a seatback within an automotive vehicle.

Claim 25 (new): An automotive seatback system as in claim 17 wherein the first panel is at least part of a seatback within an automotive vehicle.

Claim 26 (new): An automotive seatback system, comprising:

- a first panel having a main wall;
- a plurality of primary planar ribs positioned upon the first panel; and
- a plurality of channel forming ribs extending along the main wall of the first panel

an attachment system rotatably attaching the first panel to an automotive vehicle, the attachment system including:

- i) a plurality of attachment locations, each of the attachment location including at least one looped fastener;
- ii) a rod extending at least partially through the at least one looped fastener of each of the plurality of attachment locations; and
- iii) a pair of brackets attached to the vehicle and the rod.